


[multi-format video recorder]

LINE XVR 8 H.265



- “Line XVR” - a multi-format video recorder for connecting up to 8 cameras. “Line” software in a kit.

- Working with cameras of formats



Individual setting for each channel.

- The housing can accommodate two hard drives with the total volume of 24 terabytes.

► SPECIFICATION FOR ANALOG AHD/TVI/CVI/CVBS CAMERAS

Resolution of the analog camera / FPS	Processed XVR resolution / FPS	Total FPS (display/recording)	Number of channels x maximum FPS*	FPS per channel upon connection to 8 cameras*
960 H / 25	960 H / 25	200	8 x 25	25
720 P / 25	720 P / 25	200	8 x 25	25
1080 P / 25	1080 P / 25	144-150	6 x 25	18
3 MP / 18	3 MP / 18	72	4 x 18	9
4 MP / 15	4 MP / 15	60-64	4 x 15	8
4 MP / 25	1,8 MP / 25	200	8 x 25	25
5 MP / 12	5 MP / 12	48	4 x 12	6
5 MP / 20	2,5 MP / 20	80	4 x 20	10
8 MP / 15	4 MP / 15	60-64	4 x 15	8

Admintool may be used for XVR maintenance:

- Updating firmware.
- Network setup.
- Saving and restoring settings.
- Collecting service logs.

For detailed adjustment of the video server and configuring IP cameras, you can use a Line software workstation or a local management.

Various Line devices may be integrated into a single interface.

Support for the “Line Cloud” service:

- Online monitoring of the video surveillance system.
- SMS and E-mail notifications.
- DynamicDNS domain name service.
- Logging the DVR status.
- FTP archive for storing important videos.
- Connecting to the recorder without a white IP via TURN.

- Support for formats HD-TVI, AHD, CVI, CVBS and IP
- Support for 2 monitors
- Support for USB mouse
- Support for analytics in the archive
- Support for joint work with other Line software-based servers
- Support for “Line Cloud” service
- Support for “Line.Retransmitter” service
- Support for products of 152 leading manufacturers of IP cameras
- Support for two 3.5” hard drives for archive storage*



8 video channels



up to 8 audio channels


* HDD is not included into any scope of delivery of Line video recorders.

Support for ONVIF protocol and RTSP stream

Line 7 SW

Without software restrictions:

- remote monitoring and viewing the archive,
- full-fledged remote administration,
- extended user rights,
- a web server,
- viewing from mobile devices running on iOS, Android.



3 years warranty

Specifications:

operating system	Linux
network interface	100 Mbps
video outputs	1xHDMI, 1xVGA
other connections	2xUSB2.0, RS-485
analog video inputs	BNC-8
analog audio inputs	RCA-4
analog audio outputs	RCA-1
HDD	2x SATA (up to 24Tb)
operating temperature range	0...+55 °C
power	12V/4A/DC
power consumption	up to 48 W
dimensions HxWxD	54x326x250
net weight	1.2 kg