

[multi-format video recorder]
LINE XVR 4 H.265



○ “Line XVR” - a multi-format video recorder for connecting up to 4 cameras. “Line” software in a kit.

○ Working with cameras of formats



Individual setting for each channel.

○ The housing can accommodate hard drive with the volume of 12 terabytes.

► **SPECIFICATION FOR ANALOG AHD/TVI/CVI/CVBS CAMERAS**

| The resolution of analog cameras /FPS AHD/TVI/CVI/CVBS | The processed XVR resolution / FPS | 2 analog cameras display/archive FPS per channel | 3 analog cameras display/archive FPS per channel | 4 analog cameras display/archive FPS per channel |
|---|------------------------------------|--|--|--|
| 960 H / 25 fps | 960 H / 25 fps | 25 fps | 15 fps | 15 fps |
| 1-1.3 Mp / 25 fps | 1-1.3 Mp / 25 fps | 25 fps | 15 fps | 15 fps |
| 2 Mp / 25 fps | 2 Mp / 25 fps | 25 fps | 15 fps | 15 fps |
| 3 Mp / 18 fps | 3 Mp / 18 fps | 18 fps | 12 fps | 9 fps |
| 4 Mp / 15 fps | 4 Mp / 15 fps | 12 fps | 8 fps | 6 fps |
| 4 Mp / 25 fps | 1,8 Mp / 25 fps | 25 fps | 15 fps | 15 fps |
| 5 Mp / 12 fps | 5 Mp / 12 fps | 12 fps | 8 fps | 6 fps |
| 5 Mp / 25 fps | 2,5 Mp / 25 fps | 20 fps | 15 fps | 10 fps |

Admintool may be used for XVR maintenance:

- Updating firmware.
- Network setup.
- Saving and restoring settings.
- Collecting service logs.

For detailed adjustment of the video server and configuring IP cameras, you can use a Line software workstation or a local management.

Various Line devices may be integrated into a single interface.

Support for the “Line Cloud” service:

- Online monitoring of the video surveillance system.
- SMS and E-mail notifications.
- DynamicDNS domain name service.
- Logging the DVR status.
- FTP archive for storing important videos.
- Connecting to the recorder without a white IP via TURN.

- Support for formats HD-TVI, AHD, CVI, CVBS and IP
- Support for USB mouse
- Support for analytics in the archive
- Support for joint work with other Line software-based servers
- Support for “Line Cloud” service
- Support for “Line.Retransmitter” service
- Support for products of 152 leading manufacturers of IP cameras
- Support two 3.5” hard drive for archive storage*



4 video channels



4 audio channels

* HDD is not included into any scope of delivery of Line video recorders.

Support for ONVIF protocol and RTSP stream

Line 7 SW

Without software restrictions:

- remote monitoring and viewing the archive,
- full-fledged remote administration,
- extended user rights,
- a web server,
- viewing from mobile devices running on iOS, Android.



3 years warranty

Specifications:

| | |
|-----------------------------|----------------------|
| operating system | Linux |
| network interface | 100 Mbps |
| video outputs | 1xHDMI, 1xVGA |
| other connections | 2xUSB2.0, RS-485 |
| analog video inputs | BNC-4 |
| analog audio inputs | RCA-4 |
| analog audio outputs | RCA-1 |
| HDD | 1xSATA (up to 12 Tb) |
| operating temperature range | 0...+55 °C |
| power | 12V /2A/ DC |
| power consumption | up to 24 W |
| dimensions, mm | 258x230x42 |
| net weight | 0,8 kg |